



YOUR SYMBOL OF CONFIDENCE

# Product Specification Sheet



**Egoli 1**  
F1271 (STC)



## FEATURES

**Size range:** 3 - 14\*

**Upper:** Nitrile PVC Upper

**Sole:** Nitrile PVC Sole

**Colours:** White upper / White sole

**Accreditation:** SANS / EN 20345

**NRCS Approved:**  
NRCS / 9002 / 200606 / 0034

*\* please note that size 14 is a different design to sizes 3-13, but carries the same accreditations*

<b>Upper</b>	<ul style="list-style-type: none"> <li>• Nitrile PVC upper for for maximum durability</li> <li>• Reinforced ankle guard</li> <li>• Protective ribs for enhanced heel protection</li> <li>• Cut off trim ridges to allow for height adjustment</li> </ul>
<b>Sole</b>	<ul style="list-style-type: none"> <li>• Nitrile PVC sole for ultimate durability and protection against oils and chemicals</li> <li>• Cleated sole provides SRA slip-resistance rating and maximum soil release</li> </ul>
<b>Toe Cap</b>	Steel toe cap with impact resistance of 200 joules (EN 12568)
<b>Lining</b>	Nylon / Polyester fine knit liner for easy cleaning and quick drying enabling maximum hygiene
<b>Last</b>	Designed with optimal toe spring for walking and kneeling

### Optional Extras:

1. Contour moulded cushion insole for enhanced comfort and anti-fatigue support
2. Fur liner for warmth and comfort in cold environments



YOUR SYMBOL OF CONFIDENCE

# Product Specification Sheet



**Egoli 1**  
F1273 (STC) **MOQ's apply**



## FEATURES

**Size range:** 3 - 14\*

**Upper:** Nitrile PVC Upper

**Sole:** Nitrile PVC Sole

**Colours:** Yellow upper / Black sole

**Accreditation:** SANS / EN 20345

**NRCS Approved:**  
NRCS / 9002 / 200606 / 0034

*\* please note that size 14 is a different design to sizes 3-13, but carries the same accreditations*

<b>Upper</b>	<ul style="list-style-type: none"> <li>• Nitrile PVC upper for for maximum durability</li> <li>• Reinforced ankle guard</li> <li>• Protective ribs for enhanced heel protection</li> <li>• Cut off trim ridges to allow for height adjustment</li> </ul>
<b>Sole</b>	<ul style="list-style-type: none"> <li>• Nitrile PVC sole for ultimate durability and protection against oils and chemicals</li> <li>• Cleated sole provides SRA slip-resistance rating and maximum soil release</li> </ul>
<b>Toe Cap</b>	Steel toe cap with impact resistance of 200 joules (EN 12568)
<b>Lining</b>	Nylon / Polyester fine knit liner for easy cleaning and quick drying enabling maximum hygiene
<b>Last</b>	Designed with optimal toe spring for walking and kneeling

### Optional Extras:

1. Contour moulded cushion insole for enhanced comfort and anti-fatigue support
2. Fur liner for warmth and comfort in cold environments



YOUR SYMBOL OF CONFIDENCE

# Product Specification Sheet



Heavy Duty



Food Processing & Hygiene

**Egoli / F1274 (STC)**

**PVC**

**Description:** Egoli

**Colours:** Black upper with dark green sole

**Style Ref:** 1274

**Specification:** SABS & CE

**Quantity:** Pack = 10

<b>PACKING</b>	Sizes 3-4 WRB1 Wayne Sizes 5-8 WRB2 Wayne Sizes 9-13 WRB3 Wayne	440 X 440 X 260 mm 440 X 440 X 280 mm 440 X 440 X 318 mm
<b>UPPER</b>	PVC S50 N25 WHT	Shore A 58 PVC
<b>SOLE</b>	PVC S50 N25 WHT	Shore A 60 PVC
<b>SOCK LINER</b>	Nylon knit	Easy clean, rapid drying SABS 1320 Part 1
<b>TOE CAP</b>	STC 1443/9 (EG7-9)	EN12568 200 Joule Impact Resistant
<b>MIDSOLE</b>		
<b>BOOT MARKINGS</b>	Outside Leg Upper Under Sole Insert	Egoli SABS Copper foil Made in RSA
<b>BOOT LABELS</b>		
<b>CARTON MARKS</b>	Product code, boot description, size. Packer, date	

**Notes:**

1. Nitrile PVC upper for optimum flexibility and abrasion resistance
2. Nitrile PVC sole for durability and protection against fats, oils and chemicals
3. Cleated sole for SRA-level slip resistance
4. Nylon liner allows for easy cleaning and quick drying for maximum hygiene
6. Optimal toe-spring for walking and kneeling

**DETAIL PER SIZE**

Size	Height	Pair	Carton
3	357 mm	1, 723 kg	18, 3 kg
4	360 mm	1, 733 kg	18, 4 kg
5	360 mm	2, 090 kg	21, 9 kg
6	362 mm	2, 170 kg	22, 7 kg
7	370 mm	2, 356 kg	24, 6 kg
8	378 mm	2, 451 kg	25, 5 kg
9	385 mm	2, 549 kg	26, 5 kg
10	392 mm	2, 636 kg	27, 4 kg
11	400 mm	2, 872 kg	29, 6 kg
12	412 mm	2, 946 kg	30, 5 kg
13	399 mm	2, 797 kg	29, 0 kg

\* The above information is correct at time of submission but is subject to change dependent on customer/market requirements and technological improvements.